

March 2010 - International Biometrics Performance Conference

Recognition Performance in the Case of Juvenile Fingerprints



Günter Schumacher

European Commission Joint Research Centre (JRC) Institute for the Protection and Security of the Citizen (IPSC) Security Technology Assessment Unit (STA)



Motivation



March 2010 – International Biometrics Performance Conference

- Children yet to be excluded when it comes to verification against templates older than 1 or 2 years:
 - Children <12 currently not fingerprinted for neither EU passport nor Visa Information System
 - Parliament and EDPS not convinced about feasibility and accuracy performance
 - ➤ Identification and verification to be guaranteed over time, given the validity of an enrolment for about 5 years
- Biometric verification can be expected
 - > to impede child trafficking
 - > to reduce abuse of children for fraud
 - > to help identifying missed children





Current Situation



March 2010 – International Biometrics Performance Conference

3

- Matchers do not directly take into account the growing of the ridge pattern
- Resolution of scanners and assumptions about dimension of ridge structure is another obstacle
- Children fingerprinting exists only for documentation purposes but is hardly applicable to AFIS

→ Dedicated feasibility study more than overdue!



Source: Anthony's Mobile Fingerprinting



More detailed view on images



March 2010 - International Biometrics Performance Conference

/

6 years



12 years




- Ridge distance of 6 years old only half of adults: from ~10 pixels down to ~5 pixels [@500dpi]
- Likelihood of low contrast regions increase
- Quality metrics (like NFIQ) not trained for juvenile fingerprints



NFIQ: Examples from BIODEV*



March 2010 – International Biometrics Performance Conference



*BIODEV = European study on operational aspects of visa application including biometric enrolment



Why normal matchers fail




March 2010 - International Biometrics Performance Conference

6

Time =
$$T_0$$

Time =
$$T_1$$
, $T_1 >> T_0$



Difficulties in getting "still" images

Contrast problems

Wrong assumption about ridge distance

Local features displacement beyond accepted level of "distortion"



Acquisition



March 2010 – International Biometrics Performance Conference

- Can be extremely difficult to enrol young children because of inadequate scanning device and overall setup
- Need for manual help by an operator is disputable
- Time to enrol can be acceptable for first enrolment but can be inacceptable for verification
- Enrolment should become more tolerant against movements
- Touchless sensors ("on the fly") could become the ultimate choice



Image: Ultimate Woodlands




Contrast



March 2010 - International Biometrics Performance Conference

- Imprint distance between ridge lines can be down to 0.1 mm (= 2 pixel @ 500 dpi) for adults!
- Proper acquisition process can partially avoid this








Image processing



a






Raw Image

Pre-Processed

Example: Age = 6, NFIQ = 4

NIST *mindtct* finds

- √ 107 minutiae
- √ 15 minutiae have reliability score > 0.8





Matching



March 2010 - International Biometrics Performance Conference



- Matching should establish a similarity score between a template and a (kind-of) "zoomed" image
- Not yet clear whether "zooming" is linear or subject to significant distortion
- Feature extraction is usually not the same for different zooming levels of an image
- Not only minutiae positions are considered



Further facts



March 2010 – International Biometrics Performance Conference

- 500 dpi images of very young children can be excellent
 - → Elaboration on relevant conditions necessary
- Some vendors have already introduced ridge distance adoption and experimented with assumed ageing
 - → Feedback to vendors on measured growing effect
- Yet no statistics available on recognition performance against aged templates in case of juveniles
 - → Need for a test database with significant time period between enrolments of individual juvenile test subjects



Roadmap for the study



✓ Find best practice how to acquire images of sufficient quality

- ✓ Approximate ridge distance growing curve and use this for enhanced feature extraction
- ✓ Use test database to measure local feature displacement and degree of deviation from pure affine transformation
- ✓ Cooperate with vendors for introducing "juvenile feature"
- ✓ Use test database to measure performance of enhanced matchers
- ✓ Derive overall feasibility conclusion



Conclusions



March 2010 - International Biometrics Performance Conference

- Automated verification and identification of children fingerprints <u>likely to be feasible in practice</u> at acceptable performance level
- Feasibility question will be tackled in several tasks:
 - Physiological effects
 - Enrolment best practices
 - Algorithmic enhancements
 - Performance test on large data sets
- Preliminary results might become available by end of 2010



March 2010 - International Biometrics Performance Conference

Contact:

Dr. Günter Schumacher

Guenter-Egon.Schumacher@jrc.ec.europa.eu